
N-SERIES PEMA ROLLERBED

N12 2D DRIVE UNIT

BASIC ROLLERBED, 6ton CAPACITY



Technical data

Max load (ton)	6
Rolling capacity (ton)	18
Max. rotation force (kN)	8,5
Rotation speed range (mm/min)	100-2000
Diameter range min-max (mm)	250-5000
Roller diameter / total width (mm)	350 / 155
Rollers (pcs)	4
Roller material	PU
Width (mm)	680
Length (mm)	3350
Weight (kg)	750
Mains supply connection 50 Hz	3*400V+N+PE
Power (A)	16

Due to continuous R&D, Pemamek Ltd reserves the right to change the specification without notice.

PEMA N-SERIES ROLLERBEDS

PEMA N-series of conventional rollerbeds make up a range of basic solutions for rotating and handling a wide variety of cylindrical work-pieces. They occupy little space and feature a manual diameter adjustment arrangement. Loading capacities range between 12 and 1 600 tons.

PEMA N12 conventional, powered 2-roller-drive rollerbeds are reliable basic tools for rotating and moving cylindrical work-pieces such as tubes, pressure vessels and tanks in automated welding. A power unit is usually combined with one or several idler units. Thanks to their compact size, they occupy little space on shop floor.

In the N-series, roller distances are manually adjusted to accommodate varying work-piece diameters. N12 models feature quick and easy stepless manual diameter adjustment by means of a screw arrangement.

- Ideal for any cylindrical objects
- Even weight distribution
- Manual adjustment for different work-piece diameters
- PEMA rollerbeds fulfill the requirements of the European EN-safety norm
- All PEMA rollerbeds come with CE-markings

BETTER PRODUCTIVITY

A cost-effective way to improve productivity, welding quality and safety.

EASY INTEGRATION

Easy to integrate with other PEMA products like column & booms.

RELIABLE PRODUCTS


Designed and built for demanding machine shop environment.





N-SERIES PEMA ROLLERBED

N12 2D DRIVE UNIT

BASIC ROLLERBED, 6ton CAPACITY







Optional accessories

- Foot pedal for start/stop of rotation
- Foot pedal for speed control of rotation
- External control of rotation
- Rail car units

PEMAMEK LTD
Lamminkatu 47, FI-32200 Loimaa, Finland
Tel: +358 10 501 61
Email: info@pemamek.com www.pemamek.com